

CERTIFICATE OF CONFORMITY

N° 17.0153/A-1

1. Applicant

Applicant: Patrick COPIN
Manufacturer: TRACTEL S.A.S. – RD619 - BP38 Saint-Hilaire-Sous-Romilly - 10102 ROMILLY-SUR-SEINE- France

2. Equipment

Type of equipment: Anchor device Type C - EN 795:2012 and CEN/TS 16415:2013
Trade mark: TRACTEL®
Model: TRAV&MART
References: G2A – Specificity: Multi-span
G2AMP – Specificity: Single-span

3. Description

	Main characteristics:	Components:	Material:	References:
Span:	Multi: 5m min / 15m max Single: 5m min / 30m max	Flexible anchor line:	Ø 8,46mm wire rope in galvanized steel - 5x19	057252
User:	5 person (maximum load 100kg) 3 person (maximum load 150kg)	Anchor connector:	Stainless steel 316	039822
Cable tension:	100 daN	Mobile anchor: Slider	Stainless steel 431	251349
Direction of use:	Wall / floor / ceiling	Intermediate anchor – Floor / Wall:	Cupro-aluminium	193847
Angle of use:	max. 15°	Intermediate anchor – Ceiling:	Cupro-aluminium	193857
Energy absorber:	at both ends	Curve intermediate anchor (90°) – Floor / Wall:	Cupro-aluminium	193867
This device has no:	joint, entry/exit line fitting, flexible support fixed on anchor, no metallic material without evidence of durability	Curve intermediate anchor (90°) – Ceiling:	Cupro-aluminium	193877
Compatibility:	This device can be used with retractable fall arresters BLOCFOR B1.8A ESD, B1.8B ESD, B3 ESD, B6 ESD, B10 ESD, B20ESD and Guided type fall arresters including a flexible anchor line (halyard and twisted rope type) STOPFOR B and STOPFOR K.	INRS energy absorber: (x2)	Stainless steel	066688
		Tensioner:	Stainless steel 316L	040742
		Tension Indicator:	Stainless steel	066688
		Wedge end fitting:	Cupro-aluminium	193837

4. Technical referential

The assessment of conformity was conducted taking into account the provisions of:
- European standard EN 795:2012 "Personal fall protection equipment - Anchor devices".
- Technical Specification CEN/TS 16415:2013 "Personal fall protection equipment - Anchor devices - Recommendations for anchor devices for use by more than one person simultaneously" CEN/TS 16415:2013

5. Conclusion

The aforementioned anchor device type C, described in conformity report n° 17.0153, conforms to the requirements of the EN 795:2012 and CEN/TS 16415:2013.

06/01/2020
The PPE Technical Manager



This certificate cancels and replaces the one edited under the same number on 06/12/2018
This certificate includes one page. No duplicate will be issued.

This type of equipment is not a Personal Protective Equipment against falls from height, the present certificate of conformity is not an EU type examination certificate delivered by a notified body.