

## CERTIFICATE OF CONFORMITY

### N° 17.0151/A-3

### 1. Applicant

**Applicant:** Patrick COPIN  
**Manufacturer:** TRACTEL S.A.S. - RD619 - BP38 Saint-Hilaire-Sous-Romilly - 10102 ROMILLY-SUR-SEINE- France

### 2. Equipment

**Type of equipment:** Anchor device Type C - EN 795:2012 and CEN/TS 16415:2013  
**Trade mark:** TRACTEL®  
**Model:** TRAVSPRING™  
**References:** G2A – Specificity: Multi-span  
G2AMP – Specificity: Single-span

### 3. Description

	<u>Main characteristics :</u>	<u>Components :</u>	<u>Material :</u>	<u>References :</u>
Span:	Multi: 5m min / 15m max Single: 5m min / 30m max	Flexible anchor line:	Ø 8,4mm wire rope in galvanized steel - 5x19	057252
User:	5 person (maximum load 100kg) 3 person (maximum load 150kg)	Anchor connector:	Stainless steel 316	039822
Cable tension:	100 daN	Mobile anchor Connector:	Alloy steel 4135	031652
Direction of use:	Multi-span: Wall / floor Single-span: Wall / floor / Ceiling	Intermediate anchor – Floor / Wall:	Cupro-aluminium	066868
Angle of use:	max: 15°	Curve intermediate anchor (90°) – Floor / Wall:	Stainless steel 316 + Brass	066878
Energy absorber:	at both ends	Flange intermediate anchor – Floor:	Cupro-aluminium	068348
This device has no:	joint, entry/exit line fitting, flexible support fixed on anchor, no metallic material without evidence of durability	INER energy absorber:	Stainless steel (32)	066588
Compatibility:	This device can be used with retractable fall arresters BLOCFOR B1, B4, E8D, B1, B8, E8D, B5, E8D, B6, E8D, B10, E8D, B2, E8D and Guided type fall arresters including a flexible anchor line (halyard and twisted rope type) STOPFOR B and STOPFOR K.	Tensioner:	Stainless steel 316L	040742
		Tension Indicator:	Stainless steel	066858
		Wedge end fitting:	Cupro-aluminium	193837

### 4. Technical referential

The assessment of conformity was conducted taking into account the provisions of:  
- European standard EN 795:2012 "Personal fall protection equipment - Anchor devices".  
- Technical Specification CEN/TS 16415:2013 "Personal fall protection equipment - Anchor devices - Recommendations for anchor devices for use by more than one person simultaneously" CEN/TS 16415:2013

### 5. Conclusion

The aforementioned anchor device type C, described in conformity report n° 17.0151, conforms to the requirements of the EN 795:2012 and CEN/TS 16415:2013.

20/12/2019  
The PPE Technical Manager



This certificate includes one page. No duplicate will be issued.

This type of equipment is not a Personal Protective Equipment against falls from height, the present certificate of conformity is not an EU type examination certificate delivered by a notified body.